

# AI895

## Freelance hardware selector



The AI895 Analog Input Module can directly interface 2-wire transmitters and with a particular connection it can also interface 4-wire transmitters without losing the HART capability. The AI895 Analog Input Module has 8 channels. The module includes Intrinsic Safety protection components on each channel for connection to process equipment in hazardous areas without the need for additional external devices. Each channel can power and monitor a two-wire process transmitter and HART communication. The input voltage drop of the current input is typically 3 V, PTC included. The transmitter supply for each channel is able to provide at least 15 V at a 20 mA loop current to power Ex certified process transmitters and is limited to 23 mA in overload conditions.

TU890 and TU891 Compact MTU can be used with this module and it enables two wire connection to the process devices without additional terminals. TU890 for Ex applications and TU891 for non Ex applications.

## Features and benefits

- 8 channels for 4...20 mA, single ended unipolar inputs.
- HART communication.
- 1 group of 8 channels isolated from ground.
- Power and monitor for Ex certified two-wire transmitters.
- Non energy-storing analog inputs for externally powered sources.

General info	
Article number	3BSC690086R1
Type	Analog Input
Signal specification	4...20 mA
Number of channels	8
Signal type	Unipolar single ended
HART	Yes
SOE	No
Redundancy	No
High integrity	No
Intrinsic safety	Yes
Mechanics	S800

## Detailed data

Resolution	12 bit
Isolation	Groupwise isolated from ground
Under/over range	1.5 / 22 mA
Error	Typ. 0.05%, Max. 0.1%
Temperature drift	Typ. 100 ppm/°C
Input filter (rise time 0-90%)	20 ms
Current limiting	Built in current limited transmitter power
CMRR, 50Hz, 60Hz	>80 dB
NMRR, 50Hz, 60Hz	>10 dB
Rated insulation voltage	50 V
Dielectric test voltage	500 V a.c.
Power dissipation	4.75 W
Current consumption +5 V Modulebus	Typ. 130 mA
Current consumption +24 V external	Typ. 270 mA, Max. <370 mA

## Diagnostics

Front LED's	F(ault), R(un), W(arning), Tx (HART communication)
Supervision	Internal process supply

## Environment and certification

CE mark	Yes
Electrical safety	EN 61010-1, EN 61010-2-201
Hazardous Location	ATEX/IECEx Zone 2 with interface to Zone 0, cFMus C1, Div 2/Zone 2 with interface to C1, C2, C3 Div 1/Zone 0
Marine certification	ABS, BV, DNV, LR
Temperature, Operating	0 to +55 °C (+32 to +131 °F)
Temperature, Storage	-40 to +70 °C (-40 to +158 °F)
Pollution degree	Degree 2, IEC 60664-1
Corrosion protection	ISA-S71.04: G3
Relative humidity	5 to 95 %, non-condensing
Max ambient temperature	55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)
Protection class	IP20 according to IEC 60529
Mechanical operating conditions	IEC/EN 61131-2
EMC	EN 61000-6-4, 61000-6-2
Overvoltage categories	IEC/EN 60664-1, EN 50178
Equipment class	Class I according to IEC 61140; (earth protected)
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)
WEEE compliance	DIRECTIVE/2012/19/EU

## Compatibility

Use with MTU	TU890, TU891 or TU891Z
Keying code	AE

---

**Intrinsic Safety parameters**

---

U0 (Groups CENELEC USA)	IIC
I0 (Groups CENELEC USA)	IIB
P0 (Groups CENELEC USA)	IIA
U0 - C0 (uF)	0.087
U0 -L0 (mH)	4.1
U0 -L/R (uH/O)	55
I0 - C0 (uF)	0.702
I0 -L0 (mH)	16.4
I0 -L/R (uH/O)	222
P0 - C0 (uF)	2.23
P0 -L0 (mH)	32.8
P0 -L/R (uH/O)	443

---

---

**Dimensions**

---

Width	45 mm (1.77")
Depth	102 mm (4.01"), 111 mm (4.37") including connector
Height	119 mm (4.7")
Weight	0.2 kg (0.44 lbs.)

---

---

## Related products



TU890



TU891

—  
[solutions.abb/freelance](https://solutions.abb/freelance)  
[solutions.abb/controlsystems](https://solutions.abb/controlsystems)

—  
We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved