

DATA SHEET

## **DX 731F**

## Freelance hardware selector



The S700 I/O family can be used as direct I/O for AC 700F and AC 900F Freelance controllers or as PROFIBUS remote I/O with AC 700F, AC 900F, or other PROFIBUS Masters.

S700 I/O has a small footprint - the modules are featured with a high packing density, and several modules are available with inputs and outputs mixed in one module. These modules cover a wide variety of applications and give maximum flexibility. The S700 I/O is compliant with cULus and certified for installation in hazardous locations according to UL Class I, Division 2 (Groups A, B, C, and D).

The digital input/output module DX 731F has 12 channels. This module can be used as direct I/O on AC 900F and AC 700F and in addition also as Profibus Slave I/O.

## Features and benefits

- 8 digital inputs 115 230 VAC in two groups (2.0...3.3)
- 4 relay outputs (2.4...2.7), with one switch-over contact each
- as direct I/O and PROFIBUS I/O

General info		
Article number	3BDH000387R0005	
Туре	Digital Input/Output	
Life cycle status	Active	
Number of channels	12	
Signal type	Digital Input/Output	
HART	No	
SOE	No	
Redundancy	No	
Mechanics	S700	

Detailed data		
Input voltage range, "0"	-30 V+5 V	
Input voltage range, "1"	115-230 VAC	
Maximum field cable length	1000 m (shielded), 600 m (unshielded)	
Common mode voltage input	24 VDC/230 VAC	
Power dissipation	6 W	
Current consumption +24 V external	0.15 A	

Diagnostics	
Front LED's	40 LEDs for signals and error indication. One yellow LED per channel, the LED is ON when the input/output signal is high (signal 1).

Environment and certification		
CE mark	Yes	
Electrical safety	EN 50178, IEC 61131-2, UL 61010-1, UL 61010-2-201	
Hazardous Location	cULus Class 1 Div 2	
Protection rating	IP20	
Climatic operating conditions	Operation 0 +60 °C, Storage -40 +70 °C	
RoHS compliance	DIRECTIVE/2011/65/EU	
WEEE compliance	DIRECTIVE/2012/19/EU	

Dimensions		
Width	67.5 mm	
Depth	76 mm	
Height	54 mm	
Weight	300 g	



solutions.abb/freelance solutions.abb/controlsystems

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved