

DATA SHEET

CI940F

Freelance hardware selector



High-speed Ethernet communication interface module for AC 900F. Usable for PROFINET (requires Freelance 2024 or higher) or FOUNDATION FIELDBUS connected via LD 810HSE or LD 800HSE (requires Freelance 2019 SP1 FP1 or higher).

Software version Freelance 2019 SP1 FP1 or higher is mandatory.

Features and benefits

- High-speed Ethernet communication module
- PROFINET
- FOUNDATION Fieldbus HSE
- RJ-45 plug
- Support hot plug

General info		
Article number	3BDH001015R0001	
Communication protocol	PROFINET / FF-HSE Communication Module	
Life cycle status	Active	
Transmission speed	10/100 Mbit/s (full and half duplex), Auto-Negotiation and Auto MDI-X	
Line redundancy	Yes	
Hot Swap	Yes	

Detailed data		
Connector	RJ-45 plug	
24 V consumption typ.	70 mA, via 24 V terminal of CPU module	
Power dissipation	1.8 W	

Environment and certification		
Temperature, Operating	-20°C +70°C	
Temperature, Storage	-40 + 85°C	
Altitude	< 2000 m	
Corrosion protection	G3 compliant acc. ISA 71.04	
Relative humidity	max. 95%, non-condensing	
Protection class	IP20	
Emission & Immunity	EN 61000-6-4, EN 61000-6-2	
CE- marking	Yes	
Electrical Safety	IEC/EN 61010-1, IEC/EN 61010-2-201	
Hazardous location	cULus Class 1 Div 2	
RoHS compliance	Directive 2011/65/EU, (EU) 2015/863	
WEEE compliance	Directive 2012/19/EU	

Dimensions	
Width	28 mm
Height	152 mm
Depth	75 mm
Weight	145 g



solutions.abb/freelance solutions.abb/controlsystems

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved